ICX7750-26Q | RUCKUS ICX 7750-26Q



Mid-Range Core 26 Ports 40G Chassis Replacement Switch

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Ethernet switch

Product Brand RUCKUS®

General Specifications

VRF

EEE (Energy Efficient Ethernet)

Switching Capacity, maximum 2560 Gb/s

10 GbE SFP+ Ports, quantity, maximum9640 GbE QSFP Ports, quantity, maximum32Switches per Stack, maximum12

Aggregate Stack Bandwidth, maximum 5760 Gb/s

PoE/PoE+ No Stacking Yes sFlow Yes Layer 3 (STATIC, RIP, OSPF) Yes OpenFlow with Hybrid Port Mode Yes **Campus Fabric Technology** Yes **Redundant Power Option** Yes Hot Swap Internal Power Supplies & Fans Yes 802.3bt2 (90 W PoE Power per Port) No

IPsec VPN, with service module No
MACsec No
BGP Yes

Reversible Airflow Option Yes

VxLAN Yes

COMMSCOPE®

Yes

No

ICX7750-26Q | RUCKUS ICX 7750-26Q

Multi Chassis Trunking (MCT)

Yes

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted

